



4200 Series

Commercial Exit Device



AMERICAN
EAGLE
LOCK COMPANY INC.

4200 SERIES COMMERCIAL EXIT DEVICE



The American Eagle 4200 Series offers a reliable and economical solution for compliance with life safety and fire code requirements. The 4200 is available in color and architectural finishes with metal chassis cover and end cap. This device is non-handed and uses a 161 preparation for rose style trim. Function is determined by the trim selection, making the device well suited to stocking distributors. Rim and surface vertical rod applications are available to provide both security and egress.

SUGGESTED ARCHITECTURAL SPECIFICATIONS

All exit devices shall be American Eagle 4200 Series rim or surface vertical rod devices. Surface vertical rod devices to have top and bottom pullman latch bolts. Latch bolts to be dead locking where applicable. All touch bar components to be constructed of heavy gauge wrought steel or stainless steel. Devices to be furnished with metal chassis covers and end caps. Devices to be available for non-labeled doors and fire labeled doors. Devices for non-labeled doors shall have hex key dogging standard. All devices to offer a variety of trim options including pulls, standard rose trim, heavy duty rose trim, escutcheon and thumb piece trim. Fasteners to be furnished for wood and metal applications. Fire labeled devices furnished standard with sex nuts. Devices shall be listed by U.L./U.L.C. and comply with U.L. 10C and UBC 7-2 (1997) for positive pressure. All products to carry a 3-year limited warranty.

4200 SERIES SPECIFICATIONS

CHASSIS:	Cadmium plated steel
RAIL:	Heavy gauge steel or stainless steel
TOUCH PAD:	Heavy gauge steel or stainless steel
LATCH BOLT:	Stainless steel dead locking / 3/4" throw Rim / 5/8" throw SVR
PROJECTION:	2-5/8" projection
HAND:	Device is non-handed
DOGGING:	Hex key dogging standard / No dogging on fire labeled devices
APPLICATION:	Rim or surface vertical rod (7'0" tall door standard)
BACKSET:	2-3/4" / Works with 161 prep for rose trim
STILE WIDTH:	4-1/4" minimum
DOOR THICKNESS:	1-3/4"
DOOR WIDTH:	"A" size for 3'0" - 4'0" door maximum / "B" size for 2'6" - 3'0" door maximum
DEVICE FINISHES:	Aluminum, duro, gold, satin chrome, polished brass and satin stainless steel
FASTENERS:	Fasteners furnished for wood and metal door applications / Sex nuts and bolts standard with fire labeled devices
CERTIFICATION:	U.L./U.L.C. listed for "Panic", "Fire Exit Hardware" labeled for up to 1-1/2 hour for 3'0" x 7'0" maximum single, 6'0" x 7'0" maximum pairs / Complies with U.L. 10C and UBC 7.2 (1997)
WARRANTY:	Three (3) year limited warranty

TRIM SELECTION

ANSI FUNCTION	DESCRIPTION	PULL PLATE/BLANK ESCUTCHEON	NARROW ESCUTCHEON TRIM*	HEAVY DUTY WIDE ESCUTCHEON TRIM	KEY-IN-KNOB/LEVER ROSE TRIM	HEAVY DUTY KEY-IN-LEVER ROSE TRIM	GRIP PULL/THUMB PIECE**
01	Exit only, no trim or blank escutcheon.	429 PTD	—	—	—	—	—
02	Entrance by trim when actuating bar is locked down (dummy trim).	429 PUN	429 LPENX	429 LPENXH†	—	—	429 GPH
03	Entrance by trim when latch bolt is retracted by key. Key removable only when locked (night latch).	429 PUK	—	—	429 LPS	429 LPSH/ 429 LPSH-IC	429 GPG***
05	Entrance by thumb piece. Key locks or unlocks thumb piece (classroom thumb piece).	—	—	—	—	—	429 GPK
08	Entrance by knob or lever. Key unlocks knob or lever (classroom knob/lever).	—	429 LPEKF	429 LPEKFH†	429 LPK/ 429 CQK	429 LPKH/ 429 LPKH-IC	—
09	Entrance by knob or lever only when released by key. Key removable only when locked (storeroom knob/lever).	—	429 LPEKX	429 LPEKXH†	—	—	—
14	Entrance by trim when latch bolt is released by knob or lever. Always active, no cylinder (passage knob/lever).	—	429 LPENF	429 LPENFH†	429 LPN/ 429 CQN	429 LPNH	—
15	Entrance by trim when latch bolt is released by thumb piece. Always active, no cylinder (passage thumb piece).	—	—	—	—	—	429 GPN


Note: *429 LPE trim furnished with 1-1/4" mortise cylinder (1-1/8" cylinder will also work)

**429 Series Grip Pull furnished with 1-1/4" mortise cylinder (1-1/8" cylinder will also work, except GPG)


***429 GPG furnished with 1-1/4" mortise cylinder with rim tail piece

†Available 9/07


ACCESSORIES/OPTIONS




429 PTD




429 PUN




429 PUK




429 LPENX/429 LPENF




429 LPEKF/429 LPEKX




429 LPENXH/429 LPENFH†




429 LPEKFH/429 LPEKXH†




429 LPS/429 LPK




429 LPN




429 CQK




429 CQN




429 LPSH/429 LPKH




429 LPSH-IC/429 LPKH-IC




429 LPNH




429 GPH



429 GPG



429 GPK



429 GPN

Note: †Available 9/07

HOW TO ORDER

SERIES		APPLICATION		SIZE		TRIM
Exit Device Series		R – Rim V – Surface Vertical Rod		A – 3’0” to 4’0” Door B – 2’6” to 3’0” Door		Specify As Required (Example Shown)
42	00*	R	F	A	630	429LPKH
00 – Hex Key Dogging (Standard) * Dogging Not Furnished With Fire Labeled Devices		F – Fire Labeled No Designation – Egress (Panic) Labeled		689 – Aluminum 695 – Duro Bronze 696 – Gold 605 – Polished Brass 626 – Satin Chrome 630 – Satin Stainless Steel		
DOGGING		LABELING		FINISH		


ACCESSORIES/OPTIONS

PART	DESCRIPTION
429020	Top surface vertical rod for 7’0” door (furnished with SVR device)
429021	Top surface vertical rod, 1’ extension for 8’0” door (optional)
429023	Top surface vertical rod, 3’ extension for up to 10’0” door (optional)
429024	Bottom surface vertical rod (furnished with SVR device)
429001	Sex nut and bolt set (furnished standard with fire labeled device)
429002	Lock front filler (furnished with device)
429003	Strike filler (furnished with device)
429004	Rim strike w/1 ea. 1/8” shim (furnished with rim device)
429005	Top strike w/2 ea. 1/16” shims for surface vertical rod (furnished with SVR device)
429006	Bottom strike w/2 ea. 1/16” shims for surface vertical rod (furnished with SVR device)
429014	Trim back plate 2-1/2” x 8” (optional to cover 161 preparation with escutcheon trim)
429017	Trim back plate 3-1/2” x 8” (optional to cover 161 preparation with escutcheon trim)
429018	Adapter plate (furnished with standard duty rose trim)
429015	Shim, end cap, glass lite shim 1/4” (optional, must be used in conjunction with #429016)
429016	Shim, chassis, glass lite shim 1/4” (optional, must be used in conjunction with #429015)
429019	Double door strike (optional)

CROSS REFERENCE

AMERICAN EAGLE	CAL ROYAL	CORBIN/ RUSSWIN	DORMA	HAGER	MONARCH	PRECISION	SARGENT	VON DUPRIN	YALE
4200	2200	ED8000	8000	4700	19	5000	20	22	2100

No products are exactly alike. This cross reference represents our judgement of products that are most similar. Information has been obtained from trade sources. It is not represented nor guaranteed that any product exactly equals any other product.



A Division of PDQ Industries

P.O. BOX 249 • Brownstown PA 17508 • 144 Newport Road • Leola PA 17540
717.656.0174 • 866.874.3662 Toll Free • 717.656.0818 Fax

www.americaneaglelockco.com